

## Insulated container and roll Ergo 600 – 725 – 795 – 900



The versions 600, 725, 795 and 900 have been developed specifically for the transport of fresh or frozen goods, trips of short-medium term. In the standard configuration the base is suggested with 2 fixed and 2 swivel castors, the overall dimensions are limited and the reinforced frame structure is designed to absorb and distribute the force generated by non-predictable impacts in the manual handling stages. The closure in 4 or 6 points allows reliable insulation system for goods preservation at a controlled temperature, with computable and guaranteed data by ATP TuV certifications, which all models are subject. A wide range of available accessories allows to customize the containers and to satisfy the specific needs.

### Accessories

**Indoor or outdoor thermometer:** in order to check the temperature of goods.

**Polyethylene plate:** convenient blackboard where fixing destinations, messages, labels, etc.

**Plastic thread document pocket:** convenient to reach for checks and inspection.

**Side and back reinforced strip to protect against shocks:** further reinforcement of critical points subject to constant shocks in the manual handling or not.

**Base with metal feet:** availability to choose a palletized base with metal legs

**Base with metal feet:** availability to choose a palletized base with metal legs

**Stop door during load operations with integrated magnet or outdoor rubber hook:** 2 solutions in order to keep the hatch anchored to the outdoor wall during operations of load, unload and cleaning.

**Additional handle for exterior door.**

**Light shelf for eutectic plate or dry ice, load max. 30 Kg:** it is located in the upper groove and can host the eutectic plate.

**Heavy shelf for goods, load max. 150 kg:** separate goods or its weight, in order to avoid crushing problems especially for products with delicate packs.

Model	Code	Overall dimensions	Usable inside dimensions	Weight	Capacity	K Value
Ergo 600	IS00004FGA0802	750 X 810 X 1745 mm	609 X 657 X 1416 mm	Kg 82	Lt 600	0,37 W/m2k
Ergo 725	-	750 x 945 x 1745 mm	604 x 808 x 1406 mm	Kg 87	Lt 725	0,37 W/m2k
Ergo 795	-	750 x 945 x 1890 mm	604 x 811 x 1570 mm	Kg 90	Lt 795	0,37 W/m2k
Ergo 900	-	800 x 1200 x 1860 mm	612 x 1024 x 1444 mm	Kg 150	Lt 900	0,29 W/m2k