

LIGHT ELEVATING WORK PLATFORM UP TO KG 200 UPLIFT5



Model	CPS6001	CPS6002	CPS6003
Wheel diameter mm	125	150	150
Capacity kg	120	120	200
Common features to all codes			
Maximum total height m	3,96		
Maximum working total height m	5,00		
Min- max platform height m	0,86/2,96		
Platform dimensions m	0,48 x 0,68		
Dimensions when closed m	1,10 x 0,70 x 1,90		
Weight Kg	80		
Capacity in n° Operators	1		

TECHNICAL FEATURES:

- Approved for indoor use or in total absence of wind
- Entrance gate with automatic closing
- New removable base extenders
- Removable ballast (4x15 kg) (if not present the machine stops)
- Work platform measures 68.5 x 48 cm
- Pedal block brake
- Enter standard elevators and go through standard doors
- It is raised and lowered by a purely electric control (no hydraulic system is present)
- Elevation by telescopic cylinder (electric actuator)
- Equipped with 12 Volt battery with 6 Ah automatic charger
- Easy and comfortable push handling
- Also transportable up stairs by 2 people
- The machine is equipped with a handle for handling
- Non-slip checkered aluminum platform
- Labels and use and maintenance manual
- Test certificate according to the Italian and European CE regulations